

Part No. 36927

2M MINI DISPLAYPORT TO HDMI 10.2G CABLE

CONNECT MINI DISPLAYPORT DEVICES TO AN HDMI DISPLAY



DESCRIPTION

- Connects a Mini DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- Supports video mirroring and extended desktop modes
- Audio pass-through if supported by the video source
- 2 year warranty

The Lindy Mini DisplayPort to HDMI Cable is ideal for connecting a Mini DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The Mini DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

RELATED PRODUCTS

2M MINI DISPLAYPORT TO HDMI 10.2G CABLE

CONNECTORS

| | |
|-----------------------------------|---|
| Connector A | Mini DisplayPort Male |
| Connector B | HDMI Type A Male |
| Housing Material | Mini DisplayPort: PVCHDMI: PVC |
| Connector Plating | Gold plated |
| Pin Construction | Copper |
| Pin Plating | Gold plated |
| Dimensions (approx.) WxDxH | Mini DisplayPort: 17.8x10.8x7.9mm (0.7x0.43x0.31in) HDMI: 37.5x20.5x10.5mm (1.48x0.81x0.41in) |

SPECIFICATIONS

| | |
|-----------------------|--|
| Supported Bandwidth | 10.2Gbps |
| Maximum Resolution | 3840x2160@30Hz 4:4:4 8bit |
| Nominal Attenuation | 100MHz-450MHz 2.44-5.09dB 450MHz-8100MHz 5.094-32.906dB |
| Minimum Bend Radius | 50mm (1.97in) |
| Operating Temperature | 0°C - 45°C (32°F - 113°F) |
| Storage Temperature | -10°C - 80°C (14°F - 176°F) |

PURCHASING INFORMATION

| | |
|-----|---------------|
| No. | 36927 |
| EAN | 4002888369275 |

CABLE CONSTRUCTION

| | |
|--------------------|-----------------------------|
| Length | 2m (6.56ft) |
| Standard | HDMI 1.4 DisplayPort 1.2 |
| Colour | Black |
| Type | Round |
| Jacket Diameter | 4.8mm (0.19in) |
| Jacket Material | PVC |
| Conductor Material | Tinned Copper |
| Conductor Gauge | 32AWG |
| Shielding | Aluminium Braid 85% |

MISCELLANEOUS

| | |
|------------------|---|
| Packaging Type | Polybag |
| Warranty (Years) | 2 |
| Certificated | CE, UKCA, FCC, RCM, RoHS, REACH, UL & California Proposition 65 |

AVAILABLE IN OTHER LENGTHS

| |
|-----------------------|
| 36925 - 0.5m (1.64ft) |
| 36926 - 1m (3.28ft) |
| 36927 - 2m (6.56ft) |
| 36928 - 3m (9.84ft) |
| 36929 - 5m (16.44ft) |