

Part No. 41004

# **DISPLAYPORT 1.2 TO DVI CONVERTER**

CONNECTS A DISPLAYPORT SOURCE TO A DVI-D MONITOR



DESCRIPTION

- Converts a DisplayPort signal into DVI
- $\cdot$  Supports resolutions up to 1920x1080@60Hz / 1920x1200@60Hz
- Add a DVI monitor as a secondary display
- Quick and simple Plug & Play installation
- 2 year warranty

The Lindy DisplayPort 1.2 to DVI Converter is ideal for connecting a DisplayPort equipped source such as a PC or laptop to a DVI monitor. It supports high definition video resolutions up to 1920x1080@60Hz.

The converter can also be used to add another display to extend the available desktop workspace and increase productivity. Internal copper shielding provides enhanced reliability and compatibility. The converter is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug & Play installation.

RELATED PRODUCTS

0

## DISPLAYPORT 1.2 TO DVI CONVERTER



#### SPECIFICATIONS

AV Interface Interface Standard	DisplayPort to DVI DisplayPort 1.2 / DVI	Input	DisplayPort Male
Supported Bandwidth Maximum Input Resolution	10.8Gbps 1920x1080@60Hz / 1920x1200@60Hz	Output	DVI-D Female (Single Link)
Maximum Output Resolution	1920x1080@60Hz / 1920x1200@60Hz	MISCELLANEOUS	
Chipset	NXP 3361B	Packaging Type Packaging Dimension Gross Weight	Polybag 160x160x20mm (6.3x6.3x0.79in) 0.062kg (0.14lb)
HDCP Support Supported Audio	HDCP 1.4 -	Warranty (Years) Certificated	2 CE, UKCA, FCC, RCM, RoHS & REACH
Separate Audio Ports Special Features	-		

CONNECTORS

#### PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH

47.2x38.7x15.8mm (1.86x1.52x0.62in) 20x36x11mm (0.79x1.42x0.43in)/DP

### PURCHASING INFORMATION

No.	
EAN	

41004 4002888410045

#### PACKAGING CONTENTS

DisplayPort 1.2 to DVI Converter

#### Cable Length

150mm (5.91in)

Housing Material Jacket Material Jacket Diameter Minimum Bend Radius Net Weight Operating Temperature Storage Temperature Humidity Colour PVC PVC 6.5mm (0.26in) 65mm (2.56in) 0.053kg (0.12lb) -20°C - 80°C (-4°F - 176°F) -20°C - 70°C (-4°F - 158°F) 20 - 90% RH (non-condensing) Black