

Part No. 41490

IM DISPLAYPORT TO DVI CABLE

CONNECT DISPLAYPORT DEVICES TO A DVI DISPLAY



DESCRIPTION

Connects a DisplayPort equipped device to a DVI display

Supports resolutions up to 1920x1200@60Hz

 $\boldsymbol{\cdot}$ Supports video mirroring and extended desktop modes

Male to male connections for a secure direct connection

• 2 year warranty

The Lindy DisplayPort to DVI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an DVI display. It supports high definition video resolutions up to 1920x1200@60Hz.

This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

RELATED PRODUCTS

0

1M DISPLAYPORT TO DVI CABLE

CONNECTORS

Connector A Connector B Housing Material Connector Plating Pin Construction Pin Plating Dimensions (approx.) WxDxH DisplayPort Male DVI-D Male DisplayPort: ABSDVI: PVC Gold plated Copper Gold plated DisplayPort:42x22x9.4mm (1.65x0.87x0.37in) DVI: 46x39.8x15.9mm (1.81x1.57x0.63in)

CABLE CONSTRUCTION

| Length Standard | 1m (3.28ft) DVI-D (Single Link) DisplayPort 1.1 |
|--------------------|---|
| Colour | Black |
| Туре | Round |
| Jacket Diameter | 5.5mm (0.22in) |
| Jacket Material | PVC |
| Conductor Material | Tinned Copper |
| Conductor Gauge | 30AWG |
| Shielding | Aluminium Braid 85% |

SPECIFICATONS

Supported Bandwidth Maximum Resolution 1.65Gbps 1920x1200@60Hz

Nominal Attenuation

300KHz-825MHz <5dB 825MHz-2.475GHz <5dB -<12dB

Minimum Bend Radius Operating Temperature Storage Temperature 60mm (2.36in) 0°C - 45°C (32°F - 113°F) -10°C - 80°C (14°F - 176°F)

MISCELLANEOUS

Packaging Type Warranty (Years) Certificated Polybag 2 CE, FCC, RoHS, REACH, UL & California Proposition 65

PURCHASING INFORMATION

No. EAN 41490 4002888414906

AVAILABLE IN OTHER LENGTHS

41489 - 0.5m (1.64ft) 41490 - 1m (3.28ft) 41491 - 2m (6.56ft) 41492 - 3m (9.84ft) 41493 - 5m (16.44ft)

